



Technical Description – AEL-710

STYLE	AEL-710
ARTICLE - sizes - colour - weight per pair	ESD CLOG 35-47 white/grey 850 gr
SOLE - antistatic - anti-slip resistance 0,26	Polyurethane mono-density injected Between 7,5 x10(5) Ohm and 3,5 x 10 (7) Ohm sole, oil and acid resistant, anti-slip, production date
UPPER - tear strength - water vapour permeability - coefficient	“TEXFIBER” material of high perspiration Double stitching 62 N 2,1 mg/cm ² h 19,9 mg/cm ²
COLLAR PADDING	Sponge
STROEBEL	Woven-unwoven fabric, natural colour
COUNTER LINING	“ Bacteria Wall ” permanently antibacterial lining of excellent transpiration avoids the formation of bad odours and maintains the hygiene for the whole life of the fabric
VAMP LINING	Woven-unwoven felt, high sweat absorption
INSOLE	EVA ALVEOLAR antistatic anatomic covered by layer in antibacterial fabric of high absorption
COUNTER	Preformed, Thermoplastic, comfortable heel protection and support
TOECAP	Synthetic non-magnetic toe cap resistant to 200 J to EN ISO 20345:2004-S1 - elastic return
TOECAP PADDING	Woven-unwoven of synthetic latex
MARKING	EN ISO 20345:2004-S1 EPA flag
PACKAGING -box label	Ecological paper, 1 pair 10 pairs/size/carton design (style), size, colour, on every box

10 Enterprise Drive
 Carbondale, PA 18407, USA
 Tel: (570) 842-2812 Fax: (570) 842-4290
 E-Mail: bokar@bomir.com
 www.bokar.com & www.xkar.com

